

TECHNICAL DATA SHEET

Rev. 07/2026 | Page 1 of 1

PERFORMANCE LEVELS

GM DEXRON IID
ZF TE-ML 04D, 09, 14A
Voith 55.6335
Allison C-4
CAT TO-2

PACK SIZES

Multiple pack sizes
available on request.

PRODUCT FAMILY

TRULA Transmission Fluids
High-Performance Grease & Oils

MANUFACTURED BY
IBROMA LUBRICATION LTD

info@ibroma.com
www.ibroma.com

AUTOMATIC TRANSMISSION FLUID

TRULA ATF IID

Multifunctional fluid for automatic transmissions and power steering

DESCRIPTION

A modern multifunctional fluid for automatic transmissions and power steering, made from high-quality, deeply refined mineral base oils with a high viscosity index. Includes effective antioxidants, anti-wear agents, detergents, antifoam additives and special friction modifiers. Approved for power-steering systems recommending GM ATF DEXRON IID fluids, and suitable for step-shifting automatic transmissions with torque converters in cars, trucks, city and intercity buses, and road-construction and municipal machinery. Can be used in automatic transmissions from ZF, Voith and other manufacturers per the compatibility list.

COST-SAVING BENEFITS

- Enhances friction performance for smooth gear shifts
- Consistent properties throughout the operating period
- High heat capacity; stable viscosity across wide temperature ranges
- Longer drain intervals
- Excellent low-temperature performance protecting components during cold starts

TYPICAL PROPERTIES

PROPERTY	TEST METHOD	RESULT
Density at 15 °C, g/cm ³	ASTM D4052	0.865
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	7.18
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	34.5
Viscosity index	ASTM D2270	163
CCS dynamic viscosity at -40 °C, mPa·s	ASTM D2983	27,000
Flash point, open cup, °C	ASTM D92	222
Pour point, °C	ASTM D97	-46

Typical values shown do not constitute a specification. The information is based on current knowledge and is intended to describe the product for possible applications; it does not release the user from performing preliminary tests.