

TECHNICAL DATA SHEET

Rev. 07/2026 | Page 1 of 1

PERFORMANCE LEVEL

SAE 75W DCT/DSG fluids
— full OEM approvals
list opposite

PACK SIZES

Multiple pack sizes
available on request.

PRODUCT FAMILY

TRULA Transmission Fluids
High-Performance Grease & Oils

MANUFACTURED BY
IBROMA LUBRICATION LTD

info@ibroma.com
www.ibroma.com

DUAL-CLUTCH TRANSMISSION FLUID

TRULA DCT

Synthetic fluid for dry & wet dual-clutch gearboxes (DCT/DSG)

DESCRIPTION

A high-quality synthetic gear oil for pre-selective gearboxes with double 'dry' and 'wet' clutches (DCT/DSG) where the manufacturer recommends SAE 75W viscosity. A special additive package ensures excellent compatibility with synchroniser and wet-clutch materials, providing fast, smooth gear shifting per the vehicle manufacturer's recommendations.

COST-SAVING BENEFITS

- Outstanding thermal and oxidative stability
- Consistent wear protection in different operating conditions
- Enhanced fuel efficiency
- Strong resistance to high contact pressures
- High shear stability — steady viscosity throughout service life

APPROVALS & PERFORMANCE LEVELS

Aisin K111 · BMW Drivelogic 7-speed (Getrag) DCTF-1/-1+/-2, 6-speed DCT, 83 22 2 167 666 / MTF-LT-5 · BorgWarner · Bugatti Veyron · BYD DCTs Q/BYD-A1909.0058-2013 · Castrol BOT 341, BOT 351 C4, BOT 450 · Changan DCTF · Chrysler 68044345 EA & GA, Powershift 6-speed (Getrag) · Eaton PS-278 · Ferrari 7-speed (Getrag) TF DCT-3 · FIAT 9.55550-HE2, 9.55550-MZ6 · Ford/Nissan Powershift 6-speed (GFT) WSS-M2C936-A, 1490763/1490761, WSS-M2C200-D2/XT-11-QDC, WSS-M2C218-A1 · Ford F-DC, KU7J M2C218AA · Geely 7-speed · Great Wall DCT · Mitsubishi TC-SST 6-speed (GFT) MZ320065 DiaQueen SSTF-1 · Peugeot/Citroën DCS 6-speed (GFT) 9734.S2 · Porsche DCT (PDK) 999.917.080.00/.01 · Renault EDC 6-speed (Getrag), EDC-7, DC4, DW5, DW6 · Shell TF DCT-F3 · Volvo Powershift 6-speed (GFT) 1161838/1161839 · VAG (VW/Audi/Seat/Skoda) G 052 182, G 052 536, G 055 536, G 052 512, G 052 529, G 055 529; DSG 6/7-speed, S-Tronic, DQ200 (0AM/0CW), DQ250 (02E), DQ381 (0GC), DQ500 (0BH/0BT), DL501 (0B5), DQ400 (0DD)

TYPICAL PROPERTIES

PROPERTY	TEST METHOD	RESULT
Density at 15 °C, g/cm³	ASTM D4052	0.844
Kinematic viscosity at 100 °C, mm²/s	ASTM D445	6.89
Kinematic viscosity at 40 °C, mm²/s	ASTM D445	33.50
Viscosity index	ASTM D2270	172
CCS dynamic viscosity at -40 °C, mPa·s	ASTM D2983	11,300
Flash point, open cup, °C	ASTM D92	212
Pour point, °C	ASTM D97	-49

Typical values shown do not constitute a specification. The information is based on current knowledge and is intended to describe the product for possible applications; it does not release the user from performing preliminary tests.