



TECHNICAL DATA SHEET

Rev. 07/2026 | Page 1 of 1

PERFORMANCE LEVELS

MIL-PRF-81309
MIL-C-81309

PACK SIZES

5 Gallon
55-Gallon drum · IBC

PRODUCT FAMILY

Corrosion Protection
High-Performance Grease & Oils

MANUFACTURED BY IBROMA LUBRICATION LTD

info@ibroma.com
www.ibroma.com

CORROSION-PREVENTIVE COMPOUND

XT-312

Water-displacing corrosion-preventive compound and lubricant

DESCRIPTION

XT-312 is a water-displacing corrosion-preventive compound and lubricant that may be reapplied on a scheduled basis for continued protection. On exposed outdoor surfaces expect 7 - 30 days of protection depending on ambient conditions; on internal areas or in protected storage, protection can last up to one year against corrosion from humid conditions. Available in two types: Type II and Type III.

APPLICATION

Apply by dipping the parts in a vat, spraying with air or pump-type sprayers, or pouring the product over the parts. Remove protective films with a steam cleaner or by washing the parts in mineral spirits.

TYPICAL PROPERTIES

PROPERTY	TYPICAL
Appearance	Dark brown liquid
Odor	Mild waxy / solvent
Specific gravity	0.84 - 0.89
Flash point, min	~140 °F (60 °C)

Typical values shown do not constitute a specification. The information is based on current knowledge and is intended to describe the product for possible applications; it does not release the user from performing preliminary tests.